DO FEF
Automatic folding door

Safety, even in the smallest lift

Benefits at a glance
- Protects users and complies with applicable EU safety regulations
- Robust built, smoothly operating, low noise
- Requires minimal space, fits in very small lifts
- Suits any kind of lift cars
- Fits all types of existing shaft swing doors
- Quick and easy to install

Schindler DO FEF

Requires minimal space

Ideal were sliding doors do not fit

Upgrade on safety
Space and budget limitations were economic reasons in the past to build lifts without car doors and manual swing doors. But now the new European Guideline EN 81-80 (SNEL Safety Norm for Existing Lifts) stipulates the installation of a car door on existing lifts to protect passengers or goods from safety risks.

Make the most out of the available space
With a folding car door, you can use an optimum solution to solve cases where the lift or shaft is especially small and a sliding door does not fit.

If the door opening is narrow, the Schindler DO FEF may well be the ideal answer. With the robust, but extra-thin Schindler DO FEF car door, you benefit from an optimum solution for both safety and space.

Designed for easy integration
The Schindler DO FEF is installed inside the car entrance easily in very short time. Without requiring additional shaft space, its four foldable panels reduce the required space loss inside the car to a minimum. We can flexibly realise the entrance width for you in 50 mm steps.

Schindler

Safe and sound operation

The door drive unit of the Schindler DO FEF is electronically controlled and ensures smooth, low-noise and fast-response door operation. Long-life guide shoes provide for a well controlled motion.

The door panels automatically stop and reverse at the merest contact with an obstruction. If the car door is not completely open, the opening of the shaft door is being inhibited.

Design

The Schindler DO FEF is available in a 4-panel configuration and comes in two versions, stainless steel and in a range of painted colours. The central panels can be fitted with a glass window as an option.

Combines new and old, a budget-friendly investment

Aligns perfectly with the existing landing door

Guide shoes provide for a smooth door operation

Finishing in stainless steel

Technical data

Type	4 folding panels, centre opening
Entrance width (BT)	500 to 1150 mm, in 50 mm steps
Entrance height (HT)	2000 (optional 1900, 1950, 2100) mm
Finishes	Stainless steel Painted (standard colour range)
Door drive	Electronically regulated
Accessories	Glass windows on central panels
Option	Flat model design

The folding door Schindler DO FEF – a safe answer to space and budget limitations.

To suit your modernisation needs, our specialists are looking forward to advising you on the optimum solution.

Search for an office near by you:

www.schindler.com
www.schindlerlifts.co.uk

UKC.DOFEC.EN.05.10